

SCHEDULE 40 WELDED NIPPLES NPT THREADED – 304 & 316 STAINLESS STEEL



PIPE NIPPLE SPECIFICATIONS & DATA

- ASTM A-733
- ASME/ANSI B1.20.1 (pipe threading standard)
- ASTM A-530, ASTM A-312 (chemical and mechanical requirements)
- 304 & 316 stainless steel dual specification L-grade
- Manufacturing facility is ISO 9001-2008
- For Use With: Natural Gas, Steam, Oil, Water, Air
- Schedule 40 pipe is designed for low-pressure flow applications
- Fittings: Use Class 150 stainless steel
- Flanges: Use Class 150 stainless steel

Size in	Close Length (in)	Weight per Unit (lb)													
		Close	1-1/2	2	2-1/2	3	3-1/2	4	4-1/2	5	5-1/2	6	8	10	12
1/8	3/4	0.01	0.03	0.04	0.05	0.06	0.07	0.08	0.09	0.11	0.11	0.12	0.16	0.21	0.25
1/4	7/8	0.03	0.04	0.06	0.08	0.09	0.10	0.13	0.14	0.15	0.18	0.20	0.27	0.35	0.42
3/8	1	0.03	0.06	0.08	0.10	0.12	0.15	0.18	0.20	0.22	0.23	0.26	0.35	0.48	0.52
1/2	1-1/8	0.06	0.08	0.12	0.15	0.18	0.22	0.25	0.29	0.32	0.36	0.39	0.52	0.66	0.80
3/4	1-3/8	0.10	0.11	0.16	0.20	0.24	0.29	0.34	0.38	0.43	0.47	0.52	0.73	0.91	1.09
1	1-1/2	0.15		0.22	0.25	0.36	0.40	0.47	0.53	0.62	0.66	0.77	1.01	1.28	1.55
1-1/4	1-5/8	0.23		0.32	0.40	0.49	0.60	0.62	0.72	0.81	0.94	0.97	1.39	2.01	2.30
1-1/2	1-3/4	0.30		0.32	0.47	0.56	0.68	0.80	0.91	1.00	1.10	1.27	1.65	2.07	2.43
2	2	0.40			0.62	0.71	0.93	1.07	1.23	1.37	1.55	1.67	2.20	2.90	3.46
2-1/2	2-1/2	0.73				0.95	1.35	1.45	1.80	2.04	2.16	2.38	3.15	4.05	5.10
3	2-5/8	1.19				1.49	1.68	2.06	2.38	2.67	2.95	3.17	4.50	5.95	8.16
4	2-7/8	1.94						2.99	3.63	3.68	4.53	4.44	6.70	7.55	9.25
6	3-1/8	4.69						6.32				9.01			18.02