



SERVICE METAL
Trust In Every Connection

MASTER DISTRIBUTOR OF
PIPE FITTINGS & VALVES

Common Nipples Lengths Nipples Weights and Packaging Inches / Pounds

XH/Schedule 80

(Black, Galvanized, and Stainless Steel)
(PBE,TBE,TOE)



Size	Close Length	Weight per piece (lb)																
		Packing (Inner Box/Case)																
		Close	1-1/2	2	2-1/2	3	3-1/2	4	4-1/2	5	5-1/2	6	7	8	9	10	11	12
1/8	3/4	0.020	0.040	0.053	0.066	0.079	0.092	0.105		0.132		0.158						
		25/300	25/300	25/300	25/300	25/300	25/300	25/300		25/200		25/200						
1/4	7/8	0.039	0.067	0.090	0.112	0.134	0.157	0.179	0.20	0.22	0.25	0.27				0.45		0.54
		25/300	25/300	25/300	25/300	25/300	25/200	25/200	25/200	25/150	25/150	25/150				25/75		25/75
3/8	1	0.062	0.092	0.123	0.154	0.185	0.22	0.25	0.28	0.31	0.34	0.37						0.74
		25/300	25/300	25/300	25/200	25/200	25/200	25/150	25/150	25/150	25/100	25/100						25/50
1/2	1-1/8	0.102	0.136	0.181	0.23	0.27	0.32	0.36	0.41	0.45	0.50	0.54		0.73		0.91		1.09
		25/300	25/300	25/300	25/200	25/200	25/150	25/150	25/100	25/100	25/100	25/100		25/50		-/40		-/40
3/4	1-3/8	0.169	0.185	0.25	0.31	0.37	0.43	0.49	0.55	0.62	0.68	0.74	0.86	0.99	1.11	1.23		1.48
		25/200	25/200	25/150	25/150	25/100	25/100	25/75	25/75	25/50	25/50	25/50	-/40	-/40	-/40	-/25		-/25
1	1-1/2	0.27		0.36	0.45	0.54	0.64	0.73	0.82	0.91	1.00	1.09	1.27	1.45	1.63	1.81		2.18
		25/150		25/100	25/100	25/75	25/75	25/50	25/50	25/50	-/40	-/40	-/25	-/25	-/25	-/25		-/25
1-1/4	1-5/8	0.41		0.50	0.63	0.75	0.88	1.00	1.13	1.25	1.38	1.50	1.75	2.00	2.25	2.50	2.75	3.0
		25/75		25/75	25/75	25/50	25/50	25/50	-/40	-/40	-/40	-/25	-/25	-/25	-/25	-/20	-/20	-/15
1-1/2	1-3/4	0.53		0.61	0.76	0.91	1.06	1.21	1.36	1.51	1.67	1.82	2.12	2.42		3.0		3.6
		25/50		-/40	-/40	-/25	-/25	-/25	-/25	-/25	-/25	-/25	-/20	-/20		-/15		-/10
2	2	0.84			1.05	1.26	1.47	1.68	1.88	2.09	2.30	2.51	2.93	3.4	3.8	4.2	4.6	5.0
		-/40			-/25	-/25	-/20	-/20	-/20	-/20	-/15	-/15	-/10	-/10	-/10	-/10	-/6	-/6
2-1/2	2-1/2	1.28				1.92	2.24	2.56	2.88	3.2	3.5	3.8		5.1	5.8	6.4		7.7
		-/20				-/20	-/15	-/15	-/15	-/10	-/10	-/10		-/5	-/5	-/5		-/5
3	2-5/8	1.71				2.57	2.99	3.4	3.8	4.3	4.7	5.1	6.0	6.8	7.7	8.6		10.3
		-/15				-/10	-/8	-/8	-/8	-/8	-/8	-/5	-/4	-/4	-/4	-/3		-/3
3-1/2	2-3/4																	
4	2-7/8	2.50						5.0	5.6	6.2		7.5		10.0		12.5		15.0
		-/10						-/5	-/4	-/4		-/4		-/2		-/2		-/2

***NPT Threads on all nipples conform to ASME B1.20.1**