

Rack & Reel Fire Hose

INSIST ON
F P P I®

Description

Designed for interior use as replacement hose for Class II semiautomatic hose racks and reels. Light weight construction using a thermoplastic polyurethane lining and polyester jacket to prevent mold and mildew. Shipped folded for easy rack installation and complete with solid brass hose fittings. UL/ULc Listed, FM Approved.



Inspection/Replacement

Inspect or replace in accordance with NFPA1962.

Installation

Use and install in accordance with NFPA 14.

Use With:

07-500-00 Lexan Fog Nozzle
07-502-00 Brass Fog Nozzle UL/FM
07-934-00 1½" Rack Nipple
07-024-00 1½" Hose Valve UL/FM

Specifications

Single Jacket Lined Hose

Size:

1½" x 50' length
1½" x 75'
1½" x 100'

Pressure Ratings:

Service Test Pressure: 250 PSI
Bursting Pressure: 750 PSI

The information above is believed to be reliable and accurate, but meant for reference only. FPPI and its agents cannot be held responsible or liable for incidental or consequential damages or loss suffered by any person as a result of the use or misuse of any of the information or its product by any person whose methods and qualifications are beyond our control. It is the user's responsibility to assure that products and methods of use are suitable for the intended purpose, and the preparation prior to installation, and the installation is executed properly and according to existing code, regulations where applicable and accepted industry practices. If you are not trained on the installation of this product, seek guidance from a qualified installer.



3198 LIONSHEAD AVE
CARLSBAD, CA 92010
+ 1 (760) 599-1168
+ 1 (800) 344-1822
+ 1 (800) 344-3775 FAX

© 2016 Fire Protection Products, Inc.

WWW.FPPI.COM

