

Recessed Canopy Coverage Plate

INSIST ON
FPPI®

Description

Recessed Canopy Coverage Extensions provider increased coverage of the recessed canopy flange against the ceiling or wall material where it is installed. The primary purpose is to allow for increased distance between the finished surface of the building interior and the recessed sprinkler assembly. AHJs within certain earthquake zones require a minimum of 1" space between the sprinkler or sprinkler drop and the material it penetrates. Can also be used to provide coverage for oversized holes cut in finish material from previous sprinkler placements. Fits most existing recess sprinkler canopies and is compatible with all FPPI Recessed Canopies.



Installation

No tools are required for installation of the Recessed Canopy Coverage Extension. Simply slide the recessed escutcheon skirt through the ID of the coverage extension then install or re-install the recessed escutcheon skirt on to the retainer. Press the recessed skirt firmly into place against the interior surface the sprinkler penetrates without causing the interior surface to be moved or lifted by the recessed skirt/coverage extension. Follow sprinkler manufacturers instructions regarding the installation of sprinklers in recessed applications. May be used either horizontally or vertically.

Specifications

Material:
.020" Cold Rolled Steel

Standard finishes:
Chrome
White

Coverage:
5" x 1⁵/₁₆" ID

Item Numbers:
01-491 5" Coverage Chrome
01-493 5" Coverage White



3198 LIONSHEAD AVE
CARLSBAD, CA 92010
TEL +1 760 599-1168
+1 800 344-1822
FAX +1 800 344-3775

© 2012 Fire Protection Products, Inc.