

Single Inlet Connection Residential

INSIST ON
F P P I®

Description

Designed specifically for residential sprinkler systems, the Single Inlet Connection features all brass* construction with an integrally cast mounting/identification plate. The connection comes equipped with a single 1½" NST gasketed female threaded swivel inlet and a 1½" NST plug to protect the threaded swivel from damage or the introduction of foreign materials when not in use. The outlet is 1½" NPT female thread for connecting to the end of 1½" threaded male pipe. The integrated identification plate has three drilled mounting holes for attachment to a mounting surface such as an exterior wall of a building or other structure. Fasteners used should be suitable for the material to which the connection is being attached.



Installation

Install according to applicable codes using customary installation methods for the installation of threaded connections. A suitable threaded sealant such as PipeFit Thread Sealing Paste with PTFE or PTFE thread Sealant Tape should be used. Where required, a check valve should be used to maintain system pressure.

Specifications

Material:
B16 Brass*

Type:
Single Outlet PL

Sizes:
1½" FNPT x 1½" FNST

Other Specifications: Integral Identification sign "Auto Sprinkler" with mounting holes.

*Contains lead. Not for use in water systems intended for human consumption.

Now available with three different plugs:
Aluminum, Brass or ABS

09-502-00
Brass Body, Aluminum Plug

09-502-01
Brass Body, Brass Plug

09-502-02
Brass Body, ABS Plug



3198 LIONSHED AVE
CARLSBAD, CA 92010
TEL +1 760 599-1168
+1 800 344-1822
FAX +1 800 344-3775

© 2015 Fire Protection Products, Inc.

WWW.FPPI.COM

