

## Plastic (ABS) with Chain

### Description

The universal hose valve cap with chain is compatible with most 2½" sized hose valves\*. The cap is simply pushed onto the outlet, can be installed without any tools, and is engineered to be removed and put back in place several times without compromising the level of protection it delivers to the threads and against buildup of debris.

NOT SUITABLE FOR PRESSURE TESTING.

\*Not suitable for 2½" RCH Angle Hose Valve



### Installation

Make sure the valve outlet and male threads are free from debris. Push the cap onto the valve until tight. Attach chain to the valve body at the point provided by the valve manufacturer.

**CAUTION: PLASTIC HOSE VALVE CAPS ARE FOR PROTECTION OF THE MALE THREAD ONLY. DO NOT PRESSURIZE PLASTIC HOSE VALVE CAPS. SERIOUS BODILY INJURY WILL OCCUR.**

### Specifications

#### Materials:

**Cap:**  
Injection Molded ABS

**Chain, Screw and Washer:**  
Zinc plated steel

**Gasket:**  
EPDM Rubber

**Sizes:**  
2½"

**Color:**  
Red

**Inscription:**  
Do Not Pressurize

The information above is believed to be reliable and accurate, but meant for reference only. FPPI and its agents cannot be held responsible or liable for incidental or consequential damages or loss suffered by any person as a result of the use or misuse of any of the information or its product by any person whose methods and qualifications are beyond our control. It is the user's responsibility to assure that products and methods of use are suitable for the intended purpose, and the preparation prior to installation, and the installation is executed properly and according to existing code, regulations where applicable and accepted industry practices. If you are not trained on the installation of this product, seek guidance from a qualified installer.



3198 LIONSHEAD AVE  
CARLSBAD, CA 92010  
+ 1 (760) 599-1168  
+ 1 (800) 344-1822  
+ 1 (800) 344-3775 FAX

© 2016 Fire Protection Products, Inc.