

TO ORDER the correct size Fast Lok Clamps, measure the outside diameter of the hose or article and then select the next larger inside diameter clamp by catalog number.

Preformed Clamps are double wrapped and formed to a given diameter. Used primarily where one end of the hose or article is free to allow the clamps to be slid over the hose end before the fitting is inserted. All clamps may be pulled down to a smaller diameter but cannot be adjusted to a larger diameter.

PREFORMED CLAMPS (3/8" & 5/8" (NOMINAL) WIDTH) - 100/BOX



Galvanized Catalog Number	Band Width & Thickness	Clamp I.D. Inches	Stainless Steel Catalog Number	Band Width & Thick-ness
F-3	3/8 x .025	13/16"		
F-311	3/8 x .025	1-3/8"		
F-4	5/8 x .025	1"	FS-4	5/8 x .022
F-5	5/8 x .025	1-1/4"	FS-5	5/8 x .022
F-6	5/8 x .031	1-1/2"	FS-6	5/8 x .022
F-7	5/8 x .031	1-3/4"	FS-7	5/8 x .022
F-8	5/8 x .031	2"	FS-8	5/8 x .022
F-9	5/8 x .031	2-1/4"	FS-9	5/8 x .022

WITH STAINLESS STEEL LOK - 50/BOX



Galvanized Catalog Number	Band Width & Thickness	Clamp I.D. Inches	Stainless Steel Catalog Number	Band Width & Thickness
F-10	5/8 x .031	2-1/2"	FS-10	5/8 x .022
F-11	5/8 x .031	2-3/4"	FS-11	5/8 x .022
F-12	5/8 x .031	3"	FS-12	5/8 x .022
F-14	5/8 x .031	3-1/2"	FS-14	5/8 x .022

25 / BOX Minimum Order QTY

F-16	5/8 x .031	4	FS-16	5/8 x .022
F-18	5/8 x .031	4 1/2	FS-18	5/8 x .022
F-20	5/8 x .031	5	FS-20	5/8 x .022
	5/8 x .031	6	FS-24	5/8 x .022
	5/8 x .031	7	FS-28	5/8 x .022

Double-wrapped, Triple Punched, Holds Permanently

Galvanized Preformed Clamps 2-1/2 inch I.D. and above, and 5/8" wide open end clamps have a stainless steel lock for greater strength and rigidity.