

FLEXIBLE RUBBER COUPLINGS

VALVES

FLEXIBLE RUBBER COUPLINGS/ REDUCED COUPLINGS

Midland's stainless steel banded flexible rubber couplings are the perfect fit for Schedule 40 pipe applications.

Tech Specs:

- Installation torque: 60 inch lbs.
- Maximum test pressure: 4.3 PSI
- Maximum operating temperature: 140° F non-consistent
- Minimum operating temperature: - 30° F

- Corrosion-resistant & rustproof stainless steel bands.
- Durable Rubber for all Sch. 40 Pipe Applications
- Positive seal against infiltration and exfiltration
- Conforms to ASTM C 1173 and CSA B602
- Sizes 1-1/4" - 6" regular & reducing
- UPC Approved

COUPLING



REDUCING COUPLING



PART#	SIZE
195456	1-1/4"
195470	1-1/2" x 1-1/4"
195457	1-1/2"
195471	2" x 1-1/2"
195458	2"
195472	3" x 1-1/2"
195473	3" x 2"
195459	3"
195474	4" x 1-1/2"
195475	4" x 2"
195476	4" x 3"
195460	4"
195461	5"
195481	6" x 4"
195462	6"

TEST CAPS



DRAIN & TRAP CONNECTORS



PART#	SIZE
195502	1-1/2"
195510	2"
195511	3"
195512	4"

PART#	SIZE
195520	1-1/2" x 1-1/4"
195521	2" x 1-1/4"