


- Class 150 pipe fittings are UL Listed and FM Approved at 300 psi
- Class 300 pipe fittings are UL Listed
- Hot-dipped galvanized pipe fittings are certified to; NSF/ANSI 61-4 & California AB1953 Lead Free
- Malleable castings conform to ASTM A197, ASME B16.3, ASME B16.14 & ASME B16.39
- Hot-dipped galvanized pipe fittings conform to ASTM A153
- NPT threads on all pipe fittings conform to ASME B1.20.1
- Independent lab verification: fittings meet applicable chemical & physical properties.
- Manufacturing facilities are ISO 9001:2008 & ISO 14001.
- Fittings are 100% air tested.
- Canadian Registration Numbers (CRN) available

90 Degree Reducing Elbows - Black & Galvanized



Size	A (IN)	B (IN)	Weight (lb)
1/4 x 1/8	0.76	0.74	0.2
3/8 x 1/8	0.85	0.81	0.2
3/8 x 1/4	0.90	0.88	0.2
1/2 x 1/8	0.98	0.96	0.2
1/2 x 1/4	0.98	0.97	0.2
1/2 x 3/8	1.04	1.03	0.2
3/4 x 1/8	1.08	1.02	0.3
3/4 x 1/4	1.08	1.05	0.3
3/4 x 3/8	1.13	1.12	0.3
3/4 x 1/2	1.22	1.20	0.3
1 x 1/4	1.22	1.10	0.3
1 x 3/8	1.27	1.18	0.5
1 x 1/2	1.36	1.26	0.4
1 x 3/4	1.45	1.37	0.5
1-1/4 x 1/2	1.53	1.34	0.6
1-1/4 x 3/4	1.62	1.45	0.7
1-1/4 x 1	1.67	1.58	0.8
1-1/2 x 1/2	1.75	1.52	0.8
1-1/2 x 3/4	1.75	1.52	0.8
1-1/2 x 1	1.80	1.65	0.9
1-1/2 x 1-1/4	1.88	1.82	1.1
2 x 1/2	1.97	1.60	1.2
2 x 3/4	1.97	1.60	1.2
2 x 1	2.02	1.73	1.5
2 x 1-1/4	2.10	1.90	1.5
2 x 1-1/2	2.16	2.02	1.6
2-1/2 x 3/4	2.30	1.73	1.9
2-1/2 x 1	2.36	1.87	2.1
2-1/2 x 1-1/4	2.44	2.03	2.2
2-1/2 x 1-1/2	2.51	2.16	2.3
2-1/2 x 2	2.60	2.39	2.6
3 x 1/2	2.56	1.69	6.0
3 x 3/4	2.60	1.87	6.6
3 x 1	2.66	1.99	2.4
3 x 1-1/4	2.74	2.16	6.0
3 x 1-1/2	2.80	2.28	2.5
3 x 2	2.89	2.52	2.7
3 x 2-1/2	2.99	2.83	4.0
4 x 1-1/2	2.31	2.50	4.7
4 x 2	3.41	2.74	5.1
4 x 2-1/2	3.50	3.05	6.3
4 x 3	3.60	3.30	6.6